

Concepts: Electrostatic Work, Electrostatic Potential, superposition, Conservative Fields, Electrostatic Potential difference, capacitance,  $\vec{E} \approx -\frac{\Delta V}{\Delta x} \hat{x}$

(1) Find the work required to bring a charge  $q_p$  from infinity to a location  $\vec{r}_p$  in the presence of an arbitrary charge distribution which produces at  $\vec{r}_p$  an electrostatic potential  $V$ . Thus, use this to introduce the electrostatic potential.

(2) Find the electrostatic potential due to a conducting sphere of radius  $a$  (located at the origin) at a point  $\vec{r}_p$  from the center of the sphere if the sphere has a total charge  $Q$ .

(3) Determine the work required to assemble 3 charges given by:

$$(\#, q, x, y, z) = (1, 3\mu\text{C}, 1, 1, 1), (2, 6\mu\text{C}, 2, 2, 2), (3, -9\mu\text{C}, 3, 3, 3).$$

(4) The potential difference is defined as the difference in electrostatic potential between two points in space. It can also be defined as the negative work per unit charge to move a charge between two points in space.

Determine the potential difference between two plates of a ideal parallel plate capacitor with plates of area  $A$  and separation  $d$  which has a charge  $Q$  on one plate and  $-Q$  on the other plate.

(5) A parallel plate capacitor of capacitance  $C=6\mu\text{f}$  is charged to a potential difference of 200 Volts. How much energy is stored in the capacitor? If the plate separation is 0.0001m, what is the energy density of the capacitor? Then, what is the magnitude of the electric field inside the capacitor?

## Electrostatic Potential due to a Point Charge

Consider a charge located at the origin. The field from this charge is given by:

$$\vec{E}_p = k \frac{q_1}{(\vec{r}_p - \vec{r}_1)^2} \hat{r}_{1p}$$

Now, let's bring in a second charge ( $q_p$ ) from infinity and ask how much work is required to do this. The force which must be overcome is the electrostatic force and thus,

$$\vec{F}_{1p} = k \frac{q_1 q_p}{(\vec{r}_p - \vec{r}_1)^2} \hat{r}_{1p}$$

From our definition of work, we can determine this result:

$$W_{1p} = \sum_{\delta \vec{r}_p} \vec{F}_{1p} \cdot \vec{r}_p$$

The problem here is that the force is varying as you get charge  $p$  closer and closer to charge 1 (that is why I needed to include the sum sign). To answer the ultimate question of how much work is required to bring charge  $p$  to within a distance  $|\vec{r}_p - \vec{r}_1|$ , you need to add up small changes in the positions.

For non-calculus people, the result is:

$$W_{1p} = \frac{k q_1 q_p}{|\vec{r}_p|}$$

where

$$\vec{r}_{ip} \equiv \vec{r}_p - \vec{r}_i$$

We like to side-step this whole work thing though since the work really depends upon the size of the charge that you are bringing up from infinity. Instead, we define the **electrostatic potential** as

$$V \equiv \frac{W_{\infty \rightarrow |\vec{r}_{ip}|}}{q_p}$$

For the case of a single point charge  $q_i$  located at  $\vec{r}_i$ , the electrostatic potential at a point in space designated by  $\vec{r}_p$  is given by

$$V = k \frac{q_i}{|\vec{r}_p - \vec{r}_i|}$$

### This expression is very important

Furthermore, since in reality all charges are discrete, it can be argued that one obtains all other potentials by a direct superposition of individual potentials due to point charges. Often, since this is not a vector quantity, you might find it easier to calculate the potential and from there calculate the electric field. However, unless

you're a calculus student or you have a very simple situation (such as a parallel plate capacitor), you may find this task to be difficult.

Here is a nice example ... calculate the potential along the symmetry axis of the ring of charge which we had in an earlier problem on worksheet 2.

Solution:

In this case, each of the charges is the same distance from the point along the symmetry axis. Thus, if the ring is in the x-y plane and the symmetry axis is along the z-direction, we have:

$$V(z_p) = \frac{kQ}{\sqrt{z_p^2 + a^2}}$$

where the radius of the ring is a and the ring has a total charge Q.

Now, you might ask, what good is this potential?

Here is the answer (in the form of a question):

How much work is required to bring a positive test charge  $q_p$  from infinity to a distance  $z_p$  from a positively charged ring of radius a with a total charge Q?

The answer is pretty straight forward now:

$$W = q_p V = \frac{kQq_p}{\sqrt{z_p^2 + a^2}}$$

The nice thing about electrostatic potentials is this: they are conservative. This means that no matter what path you take from infinity to the desired location, if you can calculate the potential at two reference points, the work in going from the initial position to the final position is always the same (independent of path).

Now for calculus students, we can also use the potential to find the electric field easily.


Here are some details:

The electrostatic field is a **conservative vector field**. This means several important things but for now, this means that there exists a scalar potential such that if E is uniform, a connection that is particularly easy to work with is:

$$\vec{E} = -\frac{\Delta V}{\Delta x} \hat{x}$$

This is the most complicated version of this that the non-calculus students can work with.

Let's determine how much work is required to assemble a charge distribution of equal charges in the form of a square with the following descriptions:



(1, q, 0, 0, 0)

(2, q, 1, 0, 0)

(3, q, 0, 1, 0)

(4, q, 1, 1, 0)

$$W = W_{12} + W_{13} + W_{14} + W_{23} + W_{24} + W_{34}$$

In general for n charges, the work is:  $W = \frac{1}{2} \sum_{i=1}^N \sum_{\substack{j=1 \\ j \neq i}}^N W_{ij} = \frac{1}{2} \sum_{i=1}^N \sum_{\substack{j=1 \\ j \neq i}}^N \frac{kq_i q_j}{|\vec{r}_j - \vec{r}_i|}$  .

Now there is a relatively easy way to express this work: write it out as a square and then add up all the terms. Here is an example:

This work required to assemble a charge distribution of n charges can be written as:

$$W = \frac{1}{2} \begin{bmatrix} [+ ]j \rightarrow / i \downarrow & 1 & 2 & 3 & 4 & \dots & n \\ 1 & W_{11} & W_{12} & W_{13} & W_{14} & \dots & W_{1n} \\ 2 & W_{21} & W_{22} & W_{23} & W_{24} & \dots & W_{2n} \\ 3 & W_{31} & W_{32} & W_{33} & W_{34} & \dots & W_{3n} \\ 4 & W_{41} & W_{42} & W_{43} & W_{44} & \dots & W_{4n} \\ \dots & \dots & \dots & \dots & \dots & \dots & \dots \\ n & W_{n1} & W_{n2} & W_{n3} & W_{n4} & \dots & W_{nn} \end{bmatrix}$$

where my unusual sign [+ ] means that you are to add up everything inside the [ ]. I've written it here just to be clear about what you are going to be doing with the [ ]. Now,  $W_{11} = W_{22} = \dots = W_{nn} = 0$ . So the calculation is simpler and becomes:

$$W = \frac{1}{2} \begin{bmatrix} [+ ]j \rightarrow / i \downarrow & 1 & 2 & 3 & 4 & \dots & n \\ 1 & 0 & W_{12} & W_{13} & W_{14} & \dots & W_{1n} \\ 2 & W_{21} & 0 & W_{23} & W_{24} & \dots & W_{2n} \\ 3 & W_{31} & W_{32} & 0 & W_{34} & \dots & W_{3n} \\ 4 & W_{41} & W_{42} & W_{43} & 0 & \dots & W_{4n} \\ \dots & \dots & \dots & \dots & \dots & \dots & \dots \\ n & W_{n1} & W_{n2} & W_{n3} & W_{n4} & \dots & 0 \end{bmatrix}$$

Now an important property here is that if we use the entire thing in brackets, then we are counting the charges exactly twice too many times. We then can reduce the amount of our work required by recognizing that  $W_{ij} = W_{ji}$ , eliminating everything below the diagonal of zeros and multiplying by 2. The next step makes this look like the following:

$$W = \begin{bmatrix} [+ ]j \rightarrow / i \downarrow & 1 & 2 & 3 & 4 & \dots & n \\ 1 & 0 & W_{12} & W_{13} & W_{14} & \dots & W_{1n} \\ 2 & 0 & 0 & W_{23} & W_{24} & \dots & W_{2n} \\ 3 & 0 & 0 & 0 & W_{34} & \dots & W_{3n} \\ 4 & 0 & 0 & 0 & 0 & \dots & W_{4n} \\ \dots & \dots & \dots & \dots & \dots & \dots & \dots \\ n & 0 & 0 & 0 & 0 & \dots & 0 \end{bmatrix}$$

Now let's apply this to the specifics of the problem at hand. Each charge is the same and so the works involved for each charge ultimately require calculation of distances. The intermediate step showing this looks like:

$$W = \begin{bmatrix} [+ ]j \rightarrow / i \downarrow & 1 & 2 & 3 & 4 & \dots & n \\ 1 & 0 & \frac{k q_1 q_2}{r_{12}} & \frac{k q_1 q_3}{r_{13}} & \frac{k q_1 q_4}{r_{14}} & \dots & \frac{k q_1 q_n}{r_{1n}} \\ 2 & 0 & 0 & \frac{k q_2 q_3}{r_{23}} & \frac{k q_2 q_4}{r_{24}} & \dots & \frac{k q_2 q_n}{r_{2n}} \\ 3 & 0 & 0 & 0 & \frac{k q_3 q_4}{r_{34}} & \dots & \frac{k q_3 q_n}{r_{3n}} \\ 4 & 0 & 0 & 0 & 0 & \dots & \frac{k q_4 q_n}{r_{4n}} \\ \dots & \dots & \dots & \dots & \dots & \dots & \dots \\ n & 0 & 0 & 0 & 0 & \dots & 0 \end{bmatrix}$$

We thus need to calculate the various distances involved. These are given by:

$$|\vec{r}_1 - \vec{r}_2| = |\vec{r}_1 - \vec{r}_3| = |\vec{r}_2 - \vec{r}_4| = |\vec{r}_3 - \vec{r}_4| = 1 \quad \text{and} \quad |\vec{r}_1 - \vec{r}_4| = |\vec{r}_2 - \vec{r}_3| = \sqrt{2}$$

Also, in the particular problem at hand, each  $q$  is the same. Putting these inside the [ ] and factoring out the charge above then gives (for  $n=4$ ):

$$W = kq^2 \begin{bmatrix} [+ ]j \rightarrow / i \downarrow & 1 & 2 & 3 & 4 \\ 1 & 0 & \frac{1}{r_{12}} & \frac{1}{r_{13}} & \frac{1}{r_{14}} \\ 2 & 0 & 0 & \frac{1}{r_{23}} & \frac{1}{r_{24}} \\ 3 & 0 & 0 & 0 & \frac{1}{r_{34}} \\ 4 & 0 & 0 & 0 & 0 \end{bmatrix}$$

Now put in the distances to obtain:

$$W = kq^2 \begin{bmatrix} [+ ]j \rightarrow / i \downarrow & 1 & 2 & 3 & 4 \\ 1 & 0 & \frac{1}{1} & \frac{1}{1} & \frac{1}{\sqrt{2}} \\ 2 & 0 & 0 & \frac{1}{\sqrt{2}} & \frac{1}{1} \\ 3 & 0 & 0 & 0 & \frac{1}{1} \\ 4 & 0 & 0 & 0 & 0 \end{bmatrix}$$

You'll note I've eliminated everything but what is specifically involved in this example now. One small simplifying step gives:

$$W = kq^2 \begin{bmatrix} [+j \rightarrow / i \downarrow] & 1 & 2 & 3 & 4 \\ 1 & 0 & 1 & 1 & \frac{1}{\sqrt{2}} \\ 2 & 0 & 0 & \frac{1}{\sqrt{2}} & 1 \\ 3 & 0 & 0 & 0 & 1 \\ 4 & 0 & 0 & 0 & 0 \end{bmatrix}$$

Now the next step is to add up everything inside the []. This gives:

$$W = kq^2 \left[ 1 + 1 + \frac{1}{\sqrt{2}} + \frac{1}{\sqrt{2}} + 1 + 1 \right] = kq^2 \left[ 4 + \frac{2}{\sqrt{2}} \right] = kq^2 \left[ \frac{4\sqrt{2} + 2}{\sqrt{2}} \right] = 5.414kq^2$$

Let's suppose each charge was  $q = 1 \mu\text{C}$ . Then, the work required to assemble the charge distribution is given by:

$$W = 5.414 \times 8990 \times 10^{-6} \text{ J} = 0.049 \text{ J}$$

How much energy is this? If a 1 kg mass is raised through about 0.1 m, this is 1 Joule of work. In this case, it would be about a .05 kg mass raised through a distance of 0.1 m. It seems large but remember, a micro coulomb of charge is a lot of charge. If you're just dealing with a few charges, it is probably easier to write out the individual work terms and adding them rather than using the double sum notation. I've written the double sum notation here to give you a method of attack that will always work when dealing with discrete point charges. I've also provided you with a framework for evaluating this general result in a nice ordered step-by-step procedure. The only variations might be that you will need to include charge values inside the [] if the charges are different (which was not the case in this example).

Once you have this potential energy, you can answer the questions of motion for any of the charges if you know the masses to which the charges are attached.

As you can see, electric potential is a very important quantity, physically. It is good, therefore, that you understand how to calculate it, especially in simple situations.

The electrostatic potential superimposes. Thus, the potential at a point in space is given by

$$V(\vec{r}_p) = \sum_{i=1}^N V_i(\vec{r}_p - \vec{r}_i)$$

Let's look at one other way to write the work required to assemble a charge distribution.

$$W = \frac{1}{2} \sum_{i=1}^N \sum_{\substack{j=1 \\ j \neq i}}^N W_{ij} = \frac{1}{2} \sum_{i=1}^N q_i \sum_{\substack{j=1 \\ j \neq i}}^N \frac{k q_j}{|\vec{r}_j - \vec{r}_i|} = \frac{1}{2} \sum_{i=1}^n q_i V(\vec{r}_p - \vec{r}_i)$$

Here is a quick example: suppose the potential at a point in space is 5V. What is the work required to bring a  $0.5\mu\text{C}$  charge to this point? The answer is

$$W = \frac{1}{2} (0.5 \times 10^{-6})(5\text{V}) = 1.25 \times 10^{-6} \text{ J}$$

As you can see, knowing the potential at a particular point in space is useful. Of course, this is assuming that the action of bringing the charge to that location does not, in fact, change the potential that you are working against. Later, we'll need a modification for the case where separating charge changes the potential (as in a capacitor). If you have a continuous charge distribution, then the calculus modification of this is:

$$W = \frac{1}{2} \sum_{\text{all charges}} V(\vec{r}) \Delta q_i$$

Where  $V(\vec{r})$  is the potential experienced at the particular charge  $dq$  which is being integrated over. What this says is that the work required to bring a charge to a point is the product of that charge and the electrostatic potential at the point in space where that charge is located.

Seeing as the electric potential is so important, we ought to see how to calculate it.

The electric field from the long wire is:

$$\vec{E} = \frac{\lambda}{2\pi\epsilon_0 s} \hat{s}$$

The electric potential at  $r_p$  is then:

$$V = \frac{\lambda}{2\pi\epsilon_0} [\ln(a) - \ln(s)]$$

This can be obtained using the approximation  $\frac{\sum \Delta s}{s} \approx \ln(s)$ .

where  $a$  is an arbitrary point in space and  $s$  is the cylindrical distance from the wire. Don't take  $s$  to infinity and don't take  $a$  to zero.

For example, suppose  $a=10$  and  $s=5$ . Then  $\ln(10) - \ln(5) = 0.69$  (a positive value).

We can also write this as:

$$V = \frac{\lambda}{2\pi\epsilon_0} \ln\left(\frac{a}{s}\right)$$

The problem here, of course, is that we can't reference the potential to infinity or zero so I chose to reference it to a point  $a$ . That ought to be ok ... the potential is not completely determined except to within a constant. What about the potential at points along the symmetry axis of the electric dipole?

We had, for the dipole,  $\vec{E}_p = 2kq \left( \frac{a}{(a^2 + y^2)^{3/2}} \right) \hat{x}$  .

So we can determine the potential from a direct superposition of the potentials due to two point charges also. For a point charge,

$$V = k \frac{q_i}{|\vec{r}_p - \vec{r}_i|}$$

Along the y-axis, we then have:

$$\vec{r}_p = 0\hat{x} + y_p\hat{y}; \vec{r}_1 = -a\hat{x} + 0\hat{y}; \vec{r}_2 = +a\hat{x} + 0\hat{y}$$

So thus, the potential along the symmetry axis is given by:

$$V = kq \left[ \frac{-1}{\sqrt{a^2 + y_p^2}} + \frac{1}{\sqrt{a^2 + y_p^2}} \right] = 0$$

Hmmm .. of course we knew this .... If you're coming in along this axis, you are not doing work at all since the electric field points in the x direction but the displacement is in the y direction.

(1) Find the work required to bring a charge  $q_p$  from infinity to a location  $\vec{r}_p$  in the presence of an arbitrary charge distribution which produces at  $\vec{r}_p$  an electrostatic potential  $V$ . Thus, use this to introduce the electrostatic potential.

Solution: From the definition of electrostatic potential we have:

$$V \equiv \frac{W}{q_p}$$

Provided you know what the electrostatic potential for the arbitrary charge distribution is, you are then able to find the work required to move a charge close to this distribution. The result is:

$$W = V(\vec{r}_p)q_p$$

Notice that this work can be either positive or negative, depending upon the potential and the charge.

(2) Find the electrostatic potential due to a conducting sphere of radius  $a$  (located at the origin) at a point  $\vec{r}_p$  from the center of the sphere if the sphere has a total charge  $Q$ .

Solution: The sphere acts like a point charge for regions external to the sphere. From class notes, we know that the electrostatic potential of a point charge is given by:

$$V(\vec{r}_p) = k \frac{q_i}{|\vec{r}_p - \vec{r}_i|}$$

The sphere has a total charge  $Q$  and it is located at the origin. Thus, we have:

$$V(\vec{r}_p) = k \frac{Q}{|\vec{r}_p|}$$

At the surface of the sphere, the potential reaches its maximum value which is

$$V = \frac{Q}{a}$$

Since the sphere is conducting, all the charge will reside on its surface. The potential inside the sphere will be constant (**Not necessarily zero**) and equal to the value at the surface.

- (3) Determine the work required to assemble 3 charges given by:  
 $(\#, q, x, y, z) = (1, 3\mu\text{C}, 1, 1, 1), (2, 6\mu\text{C}, 2, 2, 2), (3, -9\mu\text{C}, 3, 3, 3)$ .

Solution: from class notes, we have:

$$W = \begin{bmatrix} [+]\text{j} \rightarrow / i \downarrow & 1 & 2 & 3 & 4 & \dots & n \\ 1 & 0 & \frac{kq_1q_2}{r_{12}} & \frac{kq_1q_3}{r_{13}} & \frac{kq_1q_4}{r_{14}} & \dots & \frac{kq_1q_n}{r_{1n}} \\ 2 & 0 & 0 & \frac{kq_2q_3}{r_{23}} & \frac{kq_2q_4}{r_{24}} & \dots & \frac{kq_2q_n}{r_{2n}} \\ 3 & 0 & 0 & 0 & \frac{kq_3q_4}{r_{34}} & \dots & \frac{kq_3q_n}{r_{3n}} \\ 4 & 0 & 0 & 0 & 0 & \dots & \frac{kq_4q_n}{r_{4n}} \\ \dots & \dots & \dots & \dots & \dots & \dots & \dots \\ n & 0 & 0 & 0 & 0 & \dots & 0 \end{bmatrix}$$

In this case, we have 3 charges, so this can be written as:

$$W = \begin{bmatrix} [+]\text{j} \rightarrow / i \downarrow & 1 & 2 & 3 \\ 1 & 0 & \frac{kq_1q_2}{r_{12}} & \frac{kq_1q_3}{r_{13}} \\ 2 & 0 & 0 & \frac{kq_2q_3}{r_{23}} \\ 3 & 0 & 0 & 0 \end{bmatrix} = k\mu\mu \begin{bmatrix} [+]\text{j} & \frac{18}{\sqrt{3}} & \frac{-27}{\sqrt{12}} \\ 0 & 0 & \frac{-54}{\sqrt{3}} \\ 0 & 0 & 0 \end{bmatrix} \text{ so}$$

Notice that the last row can actually be omitted because it is filled with zero's. You will also note another difference: we need to leave the charges inside the [] this time

since they are not all of the same magnitude. Notice, however, that since each is a micro, I am able to factor out that exponent. We can add this up:

$$W = 8.99 \times 10^9 \left[ \frac{18}{\sqrt{3}} - \frac{27}{\sqrt{12}} - \frac{54}{\sqrt{3}} \right] \times 10^{-12} = 8.99 \times 10^{-3} [10.392 - 7.794 - 31.117] = -0.257 \text{ J}$$

(4) The potential difference is defined as the difference in electrostatic potential between two points in space. It can also be defined as the negative work per unit charge to move a charge between two points in space.

Determine the potential difference between two plates of a ideal parallel plate capacitor with plates of area A and separation d which has a charge separation Q on one plate and -Q on the other plate. **Note: this is a very important problem. Make sure you understand it.**

Solution:

From Gauss's law, we have

$$\vec{E} = \frac{\sigma}{\epsilon_0} \hat{z}$$

between the plates of the capacitor if the positive plate is located at the origin. Since the electric field is uniform, we can easily determine the potential difference (which is often written V):

$$\Delta V = -\vec{E} \cdot \Delta \vec{z} = \frac{-\sigma(0-d)}{\epsilon_0}$$

Since the plates have an area A, and a total charge separation Q, we thus have

$$\Delta V = \frac{Qd}{A \epsilon_0}$$

The capacitance of the capacitor is defined as the (magnitude) of the ratio of the charge separation to the potential. Thus:

$$C = \frac{Q}{|\Delta V|} = \frac{Q}{\left( \frac{Qd}{\epsilon_0 A} \right)} = \epsilon_0 \frac{A}{d}$$

for the parallel plate capacitor. In passing, I'd like to mention that although we speak of "charging up a capacitor", in fact what is happening is that an electrically neutral capacitor has the charge separated from one plate to another. The capacitor is overall electrically neutral before charging and also after charging. You have, however, moved a total charge Q from one plate and placed it on the other plate.

(5) A parallel plate capacitor of capacitance  $C = 6 \mu\text{f}$  is charged to a potential difference of 200 Volts. How much energy is stored in the capacitor? If the plate separation is 0.0001m, what is the energy density of the capacitor? Then, what is the magnitude of the electric field inside the capacitor? **Note: this is a very important problem. Make sure you understand it. The concept of energy density is also extremely important to understand.**

Solution:

The potential that a given charge moves against is given by:

$$\Delta V = \frac{Q}{C}$$

where Q represents the charge that has already been moved from one plate to the other. The amount of work that is required to move a single charge q across this potential difference is given by:

$$W = q \Delta V = q \frac{Q}{C}$$

But now you notice that the potential difference across the capacitor has increased. In fact, the potential difference is now:

$$\Delta V = \frac{Q+q}{C}$$

The work required to move the next q across the capacitor is then given by:

$$W = q \frac{Q+q}{C}$$

As you can see, the work for each successive charge increases. Let me try to formulate a sequence for this (Each q is the charge on the electron or proton here ... it is really small). I am starting with a completely uncharged capacitor and moving equal sized elementary charges across one at a time, and adding up the work done for each.

$$W = 0 + q \frac{q}{C} + q \frac{2q}{C} + q \frac{3q}{C} + q \frac{4q}{C} + \dots + q \frac{Nq}{C} = \frac{q^2}{C} [0 + 1 + 2 + 3 + \dots + N] = \frac{q^2}{C} \left[ \sum_{i=1}^N i \right]$$

This is an arithmetic series.

You can look up arithmetic series at [Mathworld](http://mathworld.wolfram.com/ArithmeticSeries.html) and you will find:

$$\sum_{i=1}^N i = \frac{1}{2} N(N+1)$$

Now if n is large (it is, typically) then the sequence can be approximated as:

$$\sum_{i=1}^N i = \frac{1}{2} N^2$$

Here are some quick examples to show the validity of this approximation:

$$1+2+3+4+5 = 5+5+5 = 14 = \frac{1}{2}(5)(6) = 15; \frac{1}{2}(5^2) = 12.5 \Rightarrow 16.7\% \text{ error}$$

$$\sum_{i=1}^{1000} i = \frac{1}{2}(1000)(1001) = 500500; \frac{1}{2}(1000^2) = 500000 \Rightarrow 1\% \text{ error}$$

Normally  $N$  might be on the order of  $10^{10}$  (or more). You can see then that the approximation is pretty much valid as  $n$  gets larger (it is already good at 100). However, with the new nanotechnology advancements, you may need to get away from the approximation and add up discrete charges like this. Of course, there are still approximations involved for the potential between the plates of the capacitor. A more detailed analysis would show that the charges on the plates also spread out as much as they can so that the potential for the first few charges in fact is different than what I have represented. I'll not worry about that here. So we have the work required to be given by:

$$W = \frac{q^2}{C} \left[ \frac{N^2}{2} \right] = \frac{1}{w} \frac{[Nq]^2}{C} = \frac{Q^2}{2C}$$

Now let me show you a second approach that will give the same important result:

$$\Delta V = \frac{Q}{C}$$

The real difficulty here lies with the fact that the charges are moving against a changing potential ... every charge moved across the plates makes it harder for the next charge to be moved across the plates.

Non-calculus: We can (in a non-calculus way) answer this question then by saying that  $Q$  is moved against the **average  $V$**  (since the potential is linear in  $q$ ). Thus,

$$W = Q(\Delta V)_{\text{average}} = \frac{Q^2}{2C}$$

Thus, the total energy stored in the capacitor will be given by: ( **Very important!**)

$$U = \frac{Q^2}{2C} = \frac{1}{2} C (\Delta V)^2$$

Now, how much energy is stored in our capacitor?  $U = \frac{1}{2} \times 6 \times 10^{-6} (200)^2 = 0.12 \text{ J}$

Now for the rest of the formulation ... Since for a parallel plate capacitor, we have

$$C = \epsilon_0 \frac{A}{d}$$

we can write the stored energy as:  $U = \frac{1}{2} \epsilon_0 \frac{A}{d} (Ed)^2 = \frac{1}{2} \epsilon_0 (Ad) E^2$

The term  $Ad$  is the internal volume of the capacitor. Thus, the **energy density** of the capacitor is given by

$$u \equiv \frac{U}{\text{volume}} = \frac{1}{2} \epsilon_0 E^2$$

For our present capacitor, we can find the plate area from:

$$A = \frac{Cd}{\epsilon_0} = \frac{6 \times 10^{-6} \times 0.0001}{8.854 \times 10^{-12}} = 67.8 \text{ m}^2$$

The energy density is  $u = \frac{0.12 \text{ J}}{67.8 \times 0.0001} = 17.7 \frac{\text{J}}{\text{m}^3}$

The electric field inside is

$$E = \frac{V}{d} = \frac{200\text{V}}{0.0001\text{m}} = 2 \times 10^6 \frac{\text{V}}{\text{m}}$$

Clearly, there has got to be more to the story than I have told you. The rest involves inserting materials into the capacitor with a high dielectric constant.